

SITE PREPARATION & UNIT LOCATION

- SERVICE AS THE UNIT ITSELF. CLEARANCES SHALL BE THE SAME WIDTH
- AVOID OVERHEAD POWER LINES, OR OTHER UTILITY ACCESS TO PREVENT CONTACT OR DAMAGE DO NOT LOCATE ANY GAS FIRED EQUIPMENT NEAR
- ACCESS TO PREVENT CONTACT OR DAMAGE DO NOT LOCATE ANY GAS FIRED EQUIPMENT NEAR CORROSIVE OR EXPLOSIVE VAPORS SUCH AS ACID OR CHLORINATED VAPORS. REFER TO LOCAL CODES AND RESTRICTIONS.

NOTES:

- BASE UNIT CONSTRUCTED OF 20 GA. G90, GALVANIZED FINISH.
 FURNACE HAVE WEEP HOLES ON THE G90 GALVANIZED
- TO CURB HAVE WEEP HOLES ON THE G90 GALVANIZED PAN EXTERIOR.
- GAS INLET IS ¾" FPT
 ARES FURNACE INCLUDES A CSA CERTIFIED STAINLESS STEEL
 HEAT EXCHANGER, TWO STAGE GAS VALVE, HOT SURFACE STANDARD WARRANT IGNITION, RIGHT HAND CONTROL AND POWER VENTILATOR AS FEATURES. HEAT EXCHANGER HAS A 5 YEAR
- HOISTING POINTS ARE PART OF THE CONTROL SUSPENSION, POINTS ARE PART OF THE UNIT MOUNTING RAIL,
- SQUARE-1 OPTIONS INDOOR OR OUTDOOR KIT NOT SHOWN, SEE FURNACE FOR DETAIL, POWER VENTER RAIN SHIELD OR TO-ROUND ADAPTER SHIPPED LOOSE FOR FIELD 10 N.

0

RIMETER RAIL, 14 GA. G90, GALVANIZED FINISH



NOTE: ARES RESERVES THE RIGHT TO CHANGE SPECIFICATIONS AND PRODUCT DESIGN WITHOUT NOTICE. REVISIONS DO NOT ENTITLE THE BUYER TO CORRESPONDING CHANGES, IMPROVEMENTS, ADDITIONS OR REPLACEMENTS FOR PREVIOUSLY PURCHASED EQUIPMENT.

SUCH

350,

400

INDIRECT FIRED

GAS

UNIT TYPE

